

ActivityClassAssignmentService

Activity class related actions ...
Version: 1
BasePath: /int/ifsapplications/projection/v1/ActivityClassAssignmentService.svc
All rights reserved
<http://apache.org/licenses/LICENSE-2.0.html>

Access

1. HTTP Basic Authentication

Methods

[[Jump to Models](#)]

Table of Contents

[ActivityClassAssignments](#)

- [DELETE /ActivityClassAssignments\(ActivitySeq={ActivitySeq},ActivityClassSeq={ActivityClassSeq}\)](#)
- [GET /ActivityClassAssignments\(ActivitySeq={ActivitySeq},ActivityClassSeq={ActivityClassSeq}\)](#)
- [PATCH /ActivityClassAssignments\(ActivitySeq={ActivitySeq},ActivityClassSeq={ActivityClassSeq}\)](#)
- [GET /ActivityClassAssignments](#)
- [POST /ActivityClassAssignments](#)

[ProjectActivityClassAct](#)

- [GET /ActivityClassAssignments/IfsApp.ActivityClassAssignmentService.ProjectActivityClassAct.Default\(\)](#)

ActivityClassAssignments

DELETE /ActivityClassAssignments (ActivitySeq={ActivitySeq},ActivityClassSeq={ActivityClassSeq}) Up

Delete entity from ActivityClassAssignments (activityClassAssignmentsActivitySeqActivitySeqActivityClassSeqActivityClassSeqDelete)

Path parameters

ActivitySeq (required)
Path Parameter – key: ActivitySeq

ActivityClassSeq (required)
Path Parameter – key: ActivityClassSeq

Request headers

Return type

String

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain

Responses

202 Accepted [String](#)

204 No Content [String](#)

403 Forbidden [String](#)

404 Not found [String](#)

GET /ActivityClassAssignments (ActivitySeq={ActivitySeq},ActivityClassSeq={ActivityClassSeq}) Up

Get entity from ActivityClassAssignments by key (activityClassAssignmentsActivitySeqActivitySeqActivityClassSeqActivityClassSeqGet)

Path parameters

ActivitySeq (required)
Path Parameter – key: ActivitySeq

ActivityClassSeq (required)
Path Parameter – key: ActivityClassSeq

Query parameters

\$select (optional)
Query Parameter – Order items by property values, see OData Sorting

Return type

[ProjectActivityClassAct](#)

Example data

Content-Type: application/json

```
{
  "SubProjectId" : "It is a Text",
  "ValueDescription" : "It is a Text",
  "ProjectId" : "It is a Text",
  "keyref" : "It is a Text",
  "ActivitySeq" : 1,
  "ActivityClassId" : "It is a Text",
  "Validity" : "It is a Text",
  "Objgrants" : "It is a Text",
  "ActivityClassSeqDesc" : "It is a Text",
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "luname" : "It is a Text",
```

```
}
  "ActivityNo" : "It is a Text"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

Responses

200

response body for entity type ProjectActivityClassAct [ProjectActivityClassAct](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

PATCH /ActivityClassAssignments (ActivitySeq={ActivitySeq}, ActivityClassSeq={ActivityClassSeq}) Up

Update entity in ActivityClassAssignments (activityClassAssignmentsActivitySeqActivitySeqActivityClassSeqActivityClassSeqPatch)

Path parameters

ActivitySeq (required)

Path Parameter – key: ActivitySeq

ActivityClassSeq (required)

Path Parameter – key: ActivityClassSeq

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [ProjectActivityClassAct-Update](#) (optional)

Body Parameter – request body for updating entity type ProjectActivityClassAct

Request headers

Return type

[ProjectActivityClassAct](#)

Example data

Content-Type: application/json

```
{
  "SubProjectId" : "It is a Text",
  "ValueDescription" : "It is a Text",
  "ProjectId" : "It is a Text",
  "keyref" : "It is a Text",
  "ActivitySeq" : 1,
  "ActivityClassId" : "It is a Text",
  "Validity" : "It is a Text",
  "Objgrants" : "It is a Text",
  "ActivityClassSeqDesc" : "It is a Text",
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "luname" : "It is a Text",
  "ActivityNo" : "It is a Text"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

Responses

200

response body for entity type ProjectActivityClassAct [ProjectActivityClassAct](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

GET /ActivityClassAssignments Up

Get entities from ActivityClassAssignments (activityClassAssignmentsGet)

Query parameters

\$top (optional)

Query Parameter – Show only the first n items, see OData Paging - Top

\$skip (optional)

Query Parameter – Skip the first n items, see OData Paging - Skip

\$count (optional)

Query Parameter – Include count of items, see OData Count

\$filter (optional)

Query Parameter – Filter items by property values, see OData Filtering

Sorderby (optional)

Query Parameter – Order items by property values, see http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby>OData Sorting

Sselect (optional)

Query Parameter – Order items by property values, see http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby>OData Sorting

Return type

[inline_response_200](#)

Example data

Content-Type: application/json

```
{
  "value" : [ {
    "SubProjectId" : "It is a Text",
    "ValueDescription" : "It is a Text",
    "ProjectId" : "It is a Text",
    "keyref" : "It is a Text",
    "ActivitySeq" : 1,
    "ActivityClassId" : "It is a Text",
    "Validity" : "It is a Text",
    "Objgrants" : "It is a Text",
    "ActivityClassSeqDesc" : "It is a Text",
    "ETag" : "It is a Text",
    "Value" : "It is a Text",
    "ActivityClassSeq" : 1,
    "luname" : "It is a Text",
    "ActivityNo" : "It is a Text"
  }, {
    "SubProjectId" : "It is a Text",
    "ValueDescription" : "It is a Text",
    "ProjectId" : "It is a Text",
    "keyref" : "It is a Text",
    "ActivitySeq" : 1,
    "ActivityClassId" : "It is a Text",
    "Validity" : "It is a Text",
    "Objgrants" : "It is a Text",
    "ActivityClassSeqDesc" : "It is a Text",
    "ETag" : "It is a Text",
    "Value" : "It is a Text",
    "ActivityClassSeq" : 1,
    "luname" : "It is a Text",
    "ActivityNo" : "It is a Text"
  } ]
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

Responses

200

response body for entity array ProjectActivityClassAct [inline_response_200](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

POST /ActivityClassAssignments

Up

Add new entity to ActivityClassAssignments ([activityClassAssignmentsPost](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [ProjectActivityClassAct-Insert](#) (optional)

Body Parameter – request body for inserting entity type ProjectActivityClassAct

Request headers

Return type

[ProjectActivityClassAct](#)

Example data

Content-Type: application/json

```
{
  "SubProjectId" : "It is a Text",
  "ValueDescription" : "It is a Text",
  "ProjectId" : "It is a Text",
  "keyref" : "It is a Text",
  "ActivitySeq" : 1,
  "ActivityClassId" : "It is a Text",
  "Validity" : "It is a Text",
  "Objgrants" : "It is a Text",
  "ActivityClassSeqDesc" : "It is a Text",
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "luname" : "It is a Text",
  "ActivityNo" : "It is a Text"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

- text/plain

Responses

201
response body for entity type ProjectActivityClassAct [ProjectActivityClassAct](#)

202
Accepted [String](#)

204
No Content [String](#)

403
Forbidden [String](#)

404
Not found [String](#)

ProjectActivityClassAct

GET /ActivityClassAssignments/IfsApp.ActivityClassAssignmentService.ProjectActivityClassAct.Default

Invoke function Default (activityClassAssignmentsIfsAppActivityClassAssignmentServiceProjectActivityClassActDefaultGet)

Request headers

Query parameters

Sselect (optional)

Query Parameter – Order items by property values, see http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby>OData Sorting

Return type

[ProjectActivityClassAct](#)

Example data

Content-Type: application/json

```
{
  "SubProjectId" : "It is a Text",
  "ValueDescription" : "It is a Text",
  "ProjectId" : "It is a Text",
  "keyref" : "It is a Text",
  "ActivitySeq" : 1,
  "ActivityClassId" : "It is a Text",
  "Validity" : "It is a Text",
  "Objgrants" : "It is a Text",
  "ActivityClassSeqDesc" : "It is a Text",
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "luname" : "It is a Text",
  "ActivityNo" : "It is a Text"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

Responses

200
response body for function Default [ProjectActivityClassAct](#)

202
Accepted [String](#)

204
No Content [String](#)

403
Forbidden [String](#)

404
Not found [String](#)

Models

[[Jump to Methods](#)]

Table of Contents

1. [ConfigEntityDec](#)
2. [EntityDec](#)
3. [FndDynamicAssistSetup](#)
4. [FndDynamicAssistStep](#)
5. [FndDynamicCommandDef](#)
6. [FndDynamicNextStep](#)
7. [ProjectActivityClassAct](#)
8. [ProjectActivityClassAct-Insert - ProjectActivityClassAct for insert](#)
9. [ProjectActivityClassAct-Update - ProjectActivityClassAct for create](#)
10. [StreamInfoRec](#)
11. [inline_response_200](#)

ConfigEntityDec

ETag (optional)

[String](#)

example: It is a Text

Info (optional)

[String](#)

example: It is a Text

Attr (optional)

[String](#)

example: It is a Text

EntityDec

ETag (optional)

[String](#)

example: It is a Text

Up

Up

Up

Info (optional)

[String](#)

example: It is a Text

Attr (optional)

[String](#)

example: It is a Text

EndDynamicAssistSetup

[Up](#)

Label (optional)

[String](#)

example: It is a Text

Description (optional)

[String](#)

example: It is a Text

Entity (optional)

[String](#)

example: It is a Text

InitMetaFunction (optional)

[String](#)

example: It is a Text

StepsMetaFunction (optional)

[String](#)

example: It is a Text

FinishMetaFunction (optional)

[String](#)

example: It is a Text

NextStepFunction (optional)

[String](#)

example: It is a Text

NumberOfSteps (optional)

[BigDecimal](#)

example: 1

StartStep (optional)

[BigDecimal](#)

example: 1

EndDynamicAssistStep

[Up](#)

Label (optional)

[String](#)

example: It is a Text

StepLabel (optional)

[String](#)

example: It is a Text

Entity (optional)

[String](#)

example: It is a Text

Description (optional)

[String](#)

example: It is a Text

Name (optional)

[String](#)

example: It is a Text

Datatype (optional)

[String](#)

example: It is a Text

ControlType (optional)

[String](#)

example: It is a Text

MultiLine (optional)

[Boolean](#)

example: true

BindAttribute (optional)

[String](#)

example: It is a Text

BindAttributeLabel (optional)

[String](#)

example: It is a Text

SaveAction (optional)

[String](#)

example: It is a Text

SaveActionParameters (optional)

[String](#)

example: It is a Text

ProjectionName (optional)

[String](#)

example: It is a Text

DefaultValue (optional)

[String](#)

example: It is a Text

Required (optional)

[Boolean](#)

example: true

Enumeration (optional)

[String](#)

example: It is a Text

Reference (optional)

[String](#)

example: It is a Text

Visible (optional)

[Boolean](#)

example: true

Enabled (optional)

[Boolean](#)

example: true

RemarkNeeded (optional)

[Boolean](#)

example: true

RemarkAttribute (optional)

[String](#)

example: It is a Text

RemarkAttributeLabel (optional)

[String](#)

example: It is a Text

TerminateAllowed (optional)

[Boolean](#)

example: true

DynamicLovOptions (optional)

[String](#)

example: It is a Text

FinishEnabled (optional)

[Boolean](#)

example: true

Editable (optional)

[Boolean](#)

example: true

DefaultClobValue (optional)

[String](#)

BlobUploadCommand (optional)

[String](#)

example: It is a Text

PreviousStepAction (optional)

[String](#)

example: It is a Text

PreviousActionParameters (optional)

[String](#)

example: It is a Text

EndDynamicCommandDef

[Up](#)

Method (optional)

[String](#)

example: It is a Text

ArgName (optional)

[String](#)

example: It is a Text

ArgValue (optional)

[String](#)

example: It is a Text

Result (optional)

[String](#)

example: It is a Text

Assign (optional)

[String](#)

example: It is a Text

Next (optional)

[String](#)

example: It is a Text

Baund (optional)

[Boolean](#)

example: true

Name (optional)

[String](#)

example: It is a Text

Projection (optional)

[String](#)

example: It is a Text

Params (optional)

[String](#)

example: It is a Text

EndDynamicNextStep

[Up](#)

NextStep (optional)

[BigDecimal](#)

example: 1

DefaultValue (optional)

[String](#)

example: It is a Text

TerminateInfo (optional)

[String](#)

example: It is a Text

ProjectActivityClassAct

[Up](#)

ETag (optional)

[String](#)

example: It is a Text

luname (optional)

[String](#)

example: It is a Text

keyref (optional)

[String](#)

example: It is a Text

Objgrants (optional)

[String](#)

example: It is a Text

ActivitySeq (optional)

[BigDecimal](#)

example: 1

ActivityClassSeq (optional)

[BigDecimal](#)

example: 1

Value (optional)

[String](#)

example: It is a Text

ActivityClassId (optional)

[String](#)

example: It is a Text

ActivityClassSeqDesc (optional)

[String](#)

example: It is a Text

Validity (optional)

[String](#)

example: It is a Text

ValueDescription (optional)

[String](#)

example: It is a Text

ProjectId (optional)

[String](#)

example: It is a Text

SubProjectId (optional)

[String](#)

example: It is a Text

ActivityNo (optional)

[String](#)

example: It is a Text

ProjectActivityClassAct-Insert - ProjectActivityClassAct for insert

[Up](#)

ActivitySeq (optional)

[BigDecimal](#)

example: 1

ActivityClassSeq (optional)

[BigDecimal](#)

example: 1

Value (optional)

[String](#)

example: It is a Text

ActivityClassId (optional)

[String](#)

example: It is a Text

ActivityClassSeqDesc (optional)

[String](#)

example: It is a Text

Validity (optional)

[String](#)

example: It is a Text

ValueDescription (optional)

[String](#)

example: It is a Text

ProjectId (optional)

[String](#)

example: It is a Text

SubProjectId (optional)

[String](#)

example: It is a Text

ActivityNo (optional)

[String](#)

example: It is a Text

ProjectActivityClassAct-Update - ProjectActivityClassAct for create

[Up](#)

Value (optional)

[String](#)

example: It is a Text

ProjectId (optional)

[String](#)

example: It is a Text

SubProjectId (optional)

[String](#)

example: It is a Text

ActivityNo (optional)

[String](#)

example: It is a Text

StreamInfoRec

[Up](#)

FileName (optional)

[String](#)

example: It is a Text

MimeType (optional)

[String](#)

example: It is a Text

inline_response_200

[Up](#)

value (optional)

